

# External solid wall insulation

## Adding a thermal layer to the outside walls


Nearly half of all the heat lost from some solid-walled houses (those without a wall cavity) escapes through the walls. Insulating these walls keeps the warmth at home for longer and makes homes more comfortable and cheaper to heat.

Solid wall insulation may be suitable for a variety of wall types such as brick, stone, steel-framed and concrete construction. And, depending on the circumstances, the walls can be insulated internally (from the inside) and externally (from the outside); both are significant undertakings in terms of cost and disruption.


### How do I know if my home has solid walls?

If your home is made of brick, and the bricks have an alternating long-short-long pattern, then the walls are likely to be a solid construction with no cavity. If you can see only the long edge of the bricks, then the wall is almost certainly a cavity wall.

#### Solid wall ▼




#### Cavity wall ▼



If you can't see the pattern of the brick work then measuring the thickness of the wall at any entrance or window will help to determine the construction type. A solid brick wall is usually about 22 cm thick, a cavity wall between 27 cm and 30 cm thick, and a solid stone wall could be as much as 50 cm. The age of your home can also be a good indicator. As a general rule, if it was built before the late 1920s it is unlikely to have a cavity.

External solid-wall insulation is not a DIY task.

cont ▼



The model above shows a cut-away of external solid wall insulation applied to a non-cavity brick wall. [This kind of wall is common among houses built between around 1880 and the mid-1920s.]

#### 1 | Insulation board

This is the layer of insulation that keeps the warm air in. It is attached to the external wall of the house and protects and extends the life of the brickwork.

#### 2 | Middle section

This section, composed of a mesh between two thin layers of render, adds strength and rigidity.

#### 3 | Top layer


A final coating of cladding or render is applied to give the wall the required appearance. It brings the total thickness of the added material to between 50 and 125 mm.

#### 4 | Window sill

External fittings such as pipework and satellite dishes may need to be temporarily removed. It may be necessary to extend window sills so they protrude beyond the cladding

#### 5 | Window and frame

Windows can change in appearance, as the insulation needs to extend into the window recess.



A solid-walled urban home that has had its walls insulated externally

### What does external wall insulation involve?

External solid wall insulation involves adding a layer of insulating material to the outside walls of a building and coating this with a protective render or cladding. There are lots of options to create the finish that you want and these may even add value to your home.

External solid wall insulation may be particularly suitable if you wish to avoid internal disruption, the loss of internal space or are doing other work to the exterior of your property, such as re-rendering. It is a specialist job that requires an approved installer who will specialise in work using a specific insulation system.

### Changes to the external appearance

External solid wall insulation won't affect the size of your rooms (unlike internal solid wall insulation) but you might need planning permission as it could change the

appearance of the building. There is a wide range of colours and finishes that can be applied and all the options should be discussed with your chosen contractor. Often the existing finish can be replicated to preserve much of the original appearance of the house, but you may still need to apply for planning permission. Check with your local authority before you have any work done.

### Average costs and savings

Externally insulating your home costs on average £9,000-£13,500, though this depends on the size of the building and the number of outside walls being insulated. It is likely to be more expensive than internal wall insulation because of the cost of material and labour are higher. A typical 3-bedroom semi-detached house using gas heating could save around £235 per year on heating bills by installing external wall insulation whereas a detached house heating with oil could save around £480 per year.

### Disruption

External solid wall insulation is a significant undertaking that inevitably involves a degree of disruption. Your installer should make you aware of any particular issues but things to consider include:

- Garden access may be required and boundary walls and lean-to structures may need to be adapted or removed
- Scaffolding may need to be erected, and a space found for a skip and storage space for materials
- External fittings like rainwater pipes, satellite dishes and telephone and power cables may need to be removed and replaced afterwards
- Contractors will require water and power and the use of a toilet
- There will be a lot of noise, including power tools, and the work will generate a lot of dust and dirt



This leaflet was originally produced by the Centre for Sustainable Energy, a national charity (no. 298740) that helps people change the way they think and act on energy | [www.cse.org.uk](http://www.cse.org.uk)



Eden Rural Foyer, Old London Road  
Penrith CA11 8ET

01768 210276  
[www.cafs.org.uk](http://www.cafs.org.uk)  
[office@cafs.org.uk](mailto:office@cafs.org.uk)

Facebook /CAfsonline  
Twitter @CAfStweets

Charity Number: 1123155  
Registered Company Number: 06492907

**Cumbria Action for Sustainability (CAfs)** work to promote low carbon living, energy saving and reduced use of fossil fuels throughout Cumbria; we provide information, advice and motivation through events, site visits and practical projects.

Contact us for more information of our energy advice events and workshops and how we can help you save energy in your home.

